

The solution from Creonic for data rates of up to 1 Gbit/s offers outstanding efficiency in terms of implementation complexity. Area and energy efficiency played a decisive role during the LDPC code design process. With this unified approach not only outstanding efficiency is obtained, but also excellent error correction performance, outperforming Viterbi decoders by up to 3 dB. At the same time, a throughput of hundreds of Mbit/s can be achieved even on low-cost FPGAs.

## Benefits

- Decodes more than 5 codeword bits per clock cycle for throughputs beyond 1 Gbit/s.
- Gains up to 3 dB compared to Viterbi decoders.
- Low-power and low-complexity design.
- Layered LDPC decoder architecture, for faster convergence behavior.
- Block-to-block on-the-fly configuration.
- Early stopping criterion for iterative LDPC decoder, saving a considerable amount of energy.
- Configurable amount of LDPC decoding iterations for trading-off throughput and error correction performance.
- Collection of statistic information (number of modified information bits, number of iterations, decode success).
- LDPC encoder included.
- Available for ASIC and FPGAs (Xilinx, Altera).

## Related Products

- [802.11n/ac LDPC Decoder](#)
- [802.15.3c LDPC Decoder](#)
- [DVB-RCS2 Turbo Decoder](#)
- [DVB-S2 LDPC/BCH Encoder and Decoder](#)
- [DVB-C2 LDPC/BCH Decoder](#)

## Features

- Compliant with Multiband OFDM Physical Layer Specification, PHY Specification: Final Deliverable 1.5, August 11, 2009
- Support for all LDPC codes (approximate channel coding rates 1/2, 5/8, 3/4, 4/5)
- Support for short and long blocks (1,200 and 1,320 bits)

## Applications

- Ultra-wideband (UWB)
- Wireless USB
- Microwave Links
- Optical Links
- TeleCare / TeleHealth
- Further High-throughput Applications

## Deliverables

- VHDL source code or synthesized netlist
- HDL simulation models e.g. for Aldec's Riviera-PRO
- VHDL or SystemC testbench
- bit-accurate Matlab, C or C++ simulation model
- comprehensive documentation

## About Creonic

Creonic is an ISO 9001:2008 certified provider of ready-for-use IP cores for several algorithms of communications such as forward error correction (LDPC and Turbo coding), synchronization, and MIMO. The company offers the richest product portfolio in this field, covering standards like DVB-S2X, LTE-A, DVB-RCS2, DOCSIS 3.1, CCSDS, WiFi, WiGig, and UWB. The products are applicable for ASIC and FPGA technology and comply with the highest requirements with respect to quality and performance. For more information, please visit [www.creonic.com](http://www.creonic.com).

## Contact

Creonic GmbH  
Bahnhofstr. 26-28  
67655 Kaiserslautern  
Germany

Phone: +49 631 3435 9880  
Fax: +49 631 3435 9889  
Web: [www.creonic.com](http://www.creonic.com)  
E-mail: [sales@creonic.com](mailto:sales@creonic.com)

Twitter: [Creonic\\_IPCores](#)  
Facebook: [Creonic](#)

---